



VOYAGER RACKS dot com

Made for: Land Rover

Model: Fits 2005-2013 Range Rover Sport

Part No: VOYRRSG1VR (Low Pro, Standard)

Thank you for your recent purchase! The following is needed to install your new Voyager Rack.

- Box Knife to open packaging
- Plastic Pry-Tool
- Torx & Allen Keys
- 10mm Wrench AND 10mm Ratchet
- INCLUDED
6 Spacers (use with rails, rear of rack only)
- 8- 6mm-Bolts
- 8- Fender/Flat Washers



Step 1: Lower vehicle to access mode

Step 2: Using Pry Tool, locate and remove all 6 plugs on roof of vehicle, or remove existing rack system to expose stock rubber rails.

Step 3: Remove any dirt, previous hardware, and place spacer over each threaded hole using provided 6mm bolt. Insert into threads and START all 6 bolts.

Step 4: Lift and set rack onto vehicle, allowing head of bolts to go through corresponding hardware on rack.

Step 5: Center Rack, and remove ONE bolt at a time, ADD WASHER to each bolt, REPLACE and START bolt.

Step 6: Center rack, tighten bolts until snug, and rack does not move when grabbed/vehicle shook.



SAFETY TIP: CHECK YOUR HARDWARE AFTER EACH VOYAGE

If you have any questions, or need assistance, please email

SALES@VOYAGEROFFROAD.COM or call/text:

+1 844-NAS-RACK

Thank you for your purchase!

-Voyager
